

I CLAIM:

1. A stand adapted to stand on a supporting surface,
comprising:

5 a holding frame adapted to support an article
thereon; and

10 a plurality of spaced apart leg units, each of
which includes an upper leg and a lower leg, said
upper leg extending downwardly from said holding
frame and having an upper end connected securely
to said holding frame and a lower end opposite to
said upper end, said upper legs of said leg units
cooperatively defining a storage space below said
holding frame, said lower leg having opposite upper
and lower ends, said upper end of said lower leg
15 being pivoted to said upper leg at a position
adjacent to said lower end of said upper leg so as
to be rotatable relative to said upper leg between
a folded position, in which said lower legs of said
leg units are disposed in said storage space and
20 in which said lower ends of said upper legs are
adapted to be seated on the supporting surface, and
an extended position, in which said lower ends of
said lower legs are disposed at an elevation below
said lower ends of said upper legs and in which said
25 lower ends of said lower legs are adapted to be
seated on the supporting surface.

2. The stand as defined in Claim 1, wherein said upper

leg of each of said leg units has a pivot portion that protrudes laterally therefrom into said storage space, that is disposed adjacent to said lower end of said upper leg, and that is parallel to said holding frame, an upper abutting portion that extends downwardly and that is angled away from said pivot portion toward said lower end of said upper leg, said lower leg of each of said leg units having a lower abutting portion adjacent to said upper end of said lower leg, each of said leg units further including a pivot shaft extending transversely through said pivot portion of a respective one of said upper legs and said upper end of a respective one of said lower legs to permit turning of said lower legs about said pivot shafts between said folded and extended positions, said lower abutting portions of said lower legs respectively abutting against said upper abutting portions of said upper legs when said lower legs are disposed in said extended position.

3. The stand as defined in Claim 1, further comprising a reinforcing frame disposed below said holding frame and connected securely to said pivot portions of said upper legs so as to enhance rigidity and stability of said upper legs.

4. The stand as defined in Claim 1, wherein said holding frame is annular in shape and has a rectangular

cross-section.

5. The stand as defined in Claim 2, wherein each of said upper leg of each of said leg units includes first and second parts and a third part sandwiched between said first and second parts, each of said first, second and third parts having opposite upper and lower ends, said upper ends of said first and second parts cooperatively defining said upper end of said upper leg, said lower ends of said first, second and third parts cooperatively defining said lower end of said upper leg, said upper end of said third part defining said pivot portion of said upper leg, said lower leg of each of said leg units including first and second parts, each of which has opposite upper and lower ends, said upper ends of said first and second parts of said lower leg cooperatively defining said upper end of said lower leg, said lower ends of said first and second parts of said lower leg cooperatively defining said lower end of said lower leg, said pivot portion of said upper leg of each of said leg units being sandwiched between said upper ends of said first and second parts of the respective one of said lower legs of said leg units.
6. The stand as defined in Claim 5, wherein said holding frame is annular in shape, has a rectangular cross-section, and includes an annular inner face,

an annular outer face opposite to said annular inner face and an annular bottom face interconnecting said inner and outer faces, each of said leg units further including an L-shaped mounting bracket
5 having a horizontal portion that interconnects said upper ends of said first and second parts of a respective one of said upper legs of said leg units and said annular bottom face of said annular holding frame, and a vertical portion that extends upward
10 from said horizontal portion and that is secured to said annular inner face of said annular holding frame.